


HDMI Jumper Cables



KD-IQJUMP12FM

Female to Male HDMI jumper cable for insertion or extraction of IR or Bi-Directional RS-232, supports HDBaseT/HDMI via CAT5e/6 Digital IQ Series™ Matrix Switchers (4 per package)



Key Features

- › Enables additional MCP35™ multi-function control ports on Key Digital® Digital IQ Series™ HDBaseT/HDMI via CAT5e/6 Matrix Switchers:
 - › 8 on KD-HD4x4Lite, 12 on KD-HD6x6Lite, and 16 on KD-HD8x8Lite
- › Supports up to 75 ft. cable runs with all Champion Series™ HDMI Cables
- › Used at Source and Display end of Key Digital® Champion Series™ HDMI Cables to insert & extract IR or RS-232 control
- › Supports PCM digital or mono analog audio on ring pin.
 - › Stereo analog not suggested.
- › Disables CEC, ARC, and Ethernet over HDMI when connection is made to the 3.5mm port. CEC, ARC, and Ethernet over HDMI are active if no connection to 3.5mm port is made on Source or Display end

Specifications

- › Inputs Tx: (1) HDMI
- › Outputs Rx: (1) HDMI, (1) 3.5mm stereo for IR/RS-232
- › HDMI Signal (Video/Audio): 1.2 Volts p-p 1080p/60
- › HDMI Connector: Type A, 19 Pin Female
- › IR/RS-232 Connector: 3.5 mm stereo mini jack
- › Regulation: CE, RoHS, WEEE
- › Product: 12"
- › Weight: .35 lb.
- › 4 Units per bag



System Design Example

